



1010 Windward Ridge Parkway
Alpharetta GA 30005

Office: 770-643-8501

Fax: 770-643-8820

www.crystaltek.us

Using Vinyl-Off To Remove Clear Vinyl Shield

Read the directions on the label *and* the enclosed "How to Use Vinyl-Off" sheet. The cautions on those written materials are not repeated here but still apply.

Second, remember that heat is your friend. The product you are about to remove from your vehicle is especially thick and difficult to remove adhesive backed vinyl. It is weathered and probably appears cracked. Heat further opens the surface of the vinyl to allow Vinyl-Off to migrate thru this layer and change the adhesion to the vehicle's surface. Move the surface into direct sunlight if practical and allow it to heat up prior to beginning removal. A secondary heat source (propane torch, weed burner, even a good hair dryer or heat gun) will also assist in removal. Please use a heat source tool with which you are already familiar. Both propane torches and weed burners use exceedingly high heat and must be understood and used with extreme caution.

Just as those other instructions tell you,

- Wipe Vinyl-Off onto *only* the material to be removed.
- Allow at least 15 minutes dwell time.
- Apply your secondary heat source to about a 2 square foot area
- Lift an edge
- Remove whatever area will pull
- Keep heating the area you will remove next, lifting an edge, and pulling
- Adjust your area to be heated, the amount of heat, and the angle of your pull, based on your results (every removal is different because each surface has weathered differently)

Now, here is where the instructions differ from typical vinyl removal. *If the shield will not remove after the first application:*

- **Re-apply:** Wipe Vinyl-Off onto *only* the material to be removed, apply your heat source and re-try the removal.
- Good luck...play some good music and have a cold glass of "water" handy!

Please share with us your method to remove so we can pass along your advice to others.

Here is a different approach several users had success with; Apply near the end of your work day and reapply when you return in the morning, warm then pull. Some have had success by also roughing up the vinyl with a fine grit sandpaper to open the surface prior to applying Vinyl-Off.

FEEL FREE TO GIVE US A CALL. 8:30-5:30 M-F EST.

770-643-8501 and select sales or technical support